

MATERIAL SAFETY DATA SHEET FOR: GREAT STUFF

Replaces: Oct, 2000. Date of issue: May, 2001.

COMPANY DETAILS

Company: H. B. Fuller Company
Address: 16-22 Red Gum Drive, Dandenong South VIC 3175
Telephone: (03) 9797 6222
Emergency Telephone No: 1800 033 111

Hazardous according to criteria of Worksafe Australia

IDENTIFICATION

Product Name: Great Stuff Space Filling Foam
Other Names: Expanding polyurethane foam, AEROSOLS
Manufacturer's Code: None
UN Number: 1950
Dangerous Goods Class: 2.1
Subsidiary Risk: None
Hazchem Code: None
Poisons Schedule: Not scheduled
Packaging Group: None assigned
Use: Used for sealing cavities in walls, roofs and ceilings. Apply directly from aerosol can as instructed on the label.

Physical Description/Properties

Appearance: Beige liquid
Melting Point: Not applicable
Boiling Point: Not established
Vapour Pressure: Not established
Specific Gravity: 1.1
Flashpoint: -104°C (Estimated)

Flammability Limits: Not Established
Solubility in water: Not soluble in water

Other Properties

This product has been tested to AS 2278-1986, which requires the flammability of the propellant gasses of an aerosol to be established. Great Stuff has the classification "*Highly Flammable*" according to AS 2278. The following statement is required in commercial literature when reporting the results obtained under this standard:

"These test results on their own do not indicate the fire hazard- of the filled aerosol containers under actual fire conditions and consequently should not be applied to the assessment of fire hazard without taking into account supportive information."

MATERIAL SAFETY DATA SHEET FOR: GREAT STUFF

Replaces: Oct, 2000. Date of issue: May, 2001.

Ingredients

CHEMICAL ENTITY	CAS NO	PROPORTION
4,4-Diphenylmethane diisocyanate	101-68-8	Med
Polymeric MDI	9016-87-9	Med
Polyether polyol blend	Not available	Med-
Propane	74-98-6	Low
Isobutane	75-28-5	Low
Dimethyl ether	115-10-6	Low
Free diphenylmethane diisocyanate	101-68-8	< 0.7 %

Low <10%

Med. 10-30%

High 30-60%

V High >60%

HEALTH HAZARD INFORMATION

Risk Phrases:

R42

May cause sensitisation by inhalation

Health Effects*ACUTE:*

Swallowed:

Will cause nausea, vomiting and stomach pain if swallowed.

Eye:

Eye contact will cause irritation. Will react with moisture in eye and adhere strongly.

Skin:

Skin contact may lead to irritation. Contains residual quantities of free organic isocyanates. Contact with skin may cause dermatitis, allergic responses and, in sensitive individuals, redness, swelling and blisters. Discontinue use if irritation occurs.

Inhaled:

Possible asthma-like symptoms can occur, eg coughing, wheezing and shortness of breath, together with dizziness or headache. Inhalation will aggravate existing respiratory problems. For most individuals these symptoms are reversible.

CHRONIC:

Contains trace amounts of Diphenylmethane diisocyanate. Existing respiratory problems, such as asthma, may be aggravated by the prolonged inhalation of the vapours of this product. Repeated and prolonged contact with this product may lead to chronic dermatitis or skin and respiratory sensitisation. Sensitised individuals require only trace amounts or brief exposure to isocyanates to obtain a severe reaction. Respiratory symptoms include bronchitis, bronchial spasms, pulmonary oedema. Dermal symptoms include redness, swelling, or blisters.

First Aid

Swallowed:

If swallowed, rinse mouth thoroughly with water. Give plenty of water to drink do NOT induce vomiting. Seek medical attention.

Eyes:

If in eye, irrigate immediately with copious amounts of water for 15 minutes with eyelids held open. Seek medical advice.

MATERIAL SAFETY DATA SHEET FOR: GREAT STUFF

Replaces: Oct, 2000. Date of issue: May, 2001.

Skin:

Wash skin with plenty of soap and water. Mechanical abrasion of skin may be required to remove cured foam from skin. Remove contaminated clothing and wash before re-use. Seek medical attention if swelling, redness or blistering occurs.

Inhaled:

Remove victim from exposure - avoid becoming a casualty. Remove contaminated clothing and loosen remaining clothing. Allow patient to assume most comfortable position and keep warm. Keep at rest until fully recovered. Never give anything by mouth to an unconscious person. Seek medical attention.

First Aid Facilities:

Have eyewashes available where eye contact can occur

Advice to Doctor

Treat symptomatically. Substance is a polyurethane foam, which expands and solidifies on contact with air. Moisture on the skin or in eyes will react with this product.

PRECAUTIONS FOR USE**Safety Phrases:**

S2	Keep out of reach of children
S24	Avoid contact with skin
S45	Avoid inhaling vapours

Exposure standards [NOHSC:1003 (1995)]

Diphenylmethane Diisocyanate:
Propane:
No limits have been set for other components.

TWA

0.2mg/m³
1800 mg/m³

Engineering Controls:

General dilution ventilation in enclosed areas.

Personal Protection:

Avoid contact with bare skin. Wear overalls, safety goggles and impervious gloves. Application should be performed in conditions of adequate ventilation

Flammability:

Class 2.1 Flammable Gas. Liquid foam is highly flammable due to propellant. Cured product is not flammable once propellant has evaporated. When burnt or in contact with flame or hot surfaces, propellant gases can produce toxic gases. All potential sources of ignition, (open flames, pilot lights, furnace, spark producing switches, welding and electrical equipment etc.) must be eliminated both in and near work area. **DO NOT SMOKE WHILE USING THIS PRODUCT.** Do not incinerate or puncture the aerosol can even when empty. Always wash hands before smoking, eating, drinking or using the toilet.

SAFE HANDLING INFORMATION**Storage and Transport:**

This product is a class 2.1 flammable gas. UN 1950 AEROSOLS. Observe requirements of the Australian Code for the Transport of Dangerous Goods by Road and Rail. Keep containers securely sealed and protected against physical damage.

MATERIAL SAFETY DATA SHEET FOR: GREAT STUFFReplaces: Oct, 2000. Date of issue: May, 2001.

Store below 30°C. Do not store in direct sunlight. Avoid contamination by moisture. Keep away from open flames, sources of ignition and sources of strong heat.

Hazardous Polymerisation:

Will generate a large amount of heat when in contact with water.

Incompatibilities:

Water, amines, strong bases, chlorine, permanganate and dichromates.

Spills and Disposal:

Remove all sources of ignition, including flame, static electricity, heat and sparks. Ensure adequate ventilation; vapours are heavier than air. Allow foaming process to complete, then collect and seal in properly labelled drums. Dispose strictly in accordance with local industrial waste disposal and environmental protection regulation. Do not puncture or incinerate can, even when empty.

Fire/Explosion Hazard:

Cans exposed to fire or strong heat sources should be removed, if safe to do so. Fire fighters to wear self contained breathing apparatus if risk of exposure to vapours. Fire fighters should wear full protective equipment. Keep containers cool with water spray to avoid pressure build up and explosion. Extinguishing media: carbon dioxide, foam, water fog.

Hazardous Decomposition

Incomplete combustion can yield carbon monoxide, oxides of nitrogen and hydrogen cyanide.

OTHER INFORMATION

No data

CONTACT POINT

Technical Manager (03) 9797 6222

This MSDS summarises at the date of issue our best knowledge of the health and safety hazard information of the product, and in particular, how to safely handle and use the product in the workplace. Since H.B. Fuller Company Australia Pty Ltd cannot anticipate or control the conditions under which the product may be used, each user must, prior to usage, review this MSDS in the context of how the user intends to handle and use the product in the workplace.

If clarification or further information is needed to ensure that an appropriate assessment can be made, the user should contact this company.

Our responsibility for the products sold is subject to our standard terms and conditions, a copy of which is sent to our customers and is also available on request.
