

SUNISO 4GS REFRIGERATION OIL

Material Safety Data Sheet

SECTION I - COMPANY IDENTIFICATION

PRODUCT: SUNISO 4GS REFRIGERATION OIL

CAT. NO.: L317, L319, L322, L325

PACKED & DISTRIBUTED BY:

Virginia KMP Corporation
4100 Platinum Way
Dallas, Texas 75237

TELEPHONE NUMBERS:

Office: 1-(214) 330-7731
Emergency Only: 1-(800) 424-9300

SECTION II - HAZARDOUS INGREDIENTS

OSHA Hazardous Components (29 CFR 1910.1200)

EXPOSURE LIMITS: 8 HR. TWA

OSHA PEL

ACGIH TLV

Mineral oil (CAS# 64742-52-5)

NE

5 mg/m³ (mist)

SECTION III - HAZARDS IDENTIFICATIONS

EMERGENCY OVERVIEW: CAUTION! Eye and skin irritant. Harmful if swallowed.

POTENTIAL HEALTH EFFECTS:

INHALATION: Harmful if inhaled, but unlikely in normal use.
EYE CONTACT: Eye irritation develops immediately upon contact.
SKIN CONTACT: Causes skin irritation; may aggravate pre-existing skin disorders.
INGESTION: Irritates gastrointestinal tract.

CHRONIC Effects: None Established

NOTE:

CARCINOGENICITY: LISTED IN NTP? No
Regulated? No

IARC? No

OSHA

SECTION IV - FIRST AID MEASURES

INHALATION: Remove victim to fresh air and, if needed, immediately begin artificial respiration. Give oxygen if breathing is labored. Get emergency medical help. Contact a physician immediately.
EYE CONTACT: Flush eyes with water for 15 minutes. Get medical attention if symptoms develop and persist.
SKIN CONTACT: Flush with water or soap and water for 15 minutes or until all traces have been removed. Seek medical attention if symptoms develop and persist.
INGESTION: Do NOT induce vomiting. Rinse mouth out with water. Get immediate medical attention.

SECTION V - FIRE FIGHTING MEASURES

FLASHPOINT (TEST METHOD): 302 F
FLAMMABLE LIMITS: LOWER: ND UPPER: ND
AUTOIGNITION TEMPERATURE: ND

GENERAL HAZARD: Combustible liquid, acrid smoke and irritating fumes.
FIRE FIGHTING INSTRUCTIONS: Keep unnecessary people away; isolate area. Firefighters should wear NIOSH approved, self contained breathing apparatus. Approach fire from upwind side. Avoid breathing smoke, fumes, mist, or vapors on the downwind side.

EXTINGUISHING MEDIA: Dry powder, carbon dioxide (CO₂), water fog or spray.
HAZARDOUS COMBUSTION PRODUCTS: Smoke, carbon monoxide, carbon dioxide.

SECTION VI - ACCIDENTAL RELEASE MEASURES

LAND SPILL: Emergency response coordinator must have mandated training. Eliminate all ignition sources. **SMALL SPILLS:** Pick up with absorbent materials and place in non-leaking containers; seal tightly for proper disposal or reuse. **LARGE SPILLS:** Evacuate the hazard area of unprotected personnel. Wear appropriate respirator and protective clothing. Shut off source of leak if safe to do so. Dike and contain. Remove with vacuum trucks or pump to storage/salvage vessels.

WATER SPILL: Floating water hazard. Collect and place in chemical waste container. Notify appropriate authorities.

Clean up leaks/spills immediately to prevent soil or water contamination.

SECTION VII - HANDLING AND STORAGE

HANDLING: After handling this product, wash hands before eating, drinking, or smoking. Avoid contact with skin, eyes, and clothing. If contact occurs, remove contaminated clothing. If needed, take first aid action shown in Section IV. Launder contaminated clothing before reuse.

STORAGE: Store away from oxidizers. Store away from sources of ignition.

SUNISO 4GS REFRIGERATION OIL

SECTION VIII - EXPOSURE CONTROLS/PERSONAL PROTECTION

ENGINEERING CONTROLS: Local exhaust ventilation recommended.

PERSONAL PROTECTION: Use gloves to prevent prolonged skin contact.

SECTION IX - PHYSICAL AND CHEMICAL PROPERTIES

VAPOR PRESSURE: Negligible

SPECIFIC GRAVITY: 0.9

SOLUBILITY IN WATER: Insoluble

pH: NA

BOILING POINT: 260 C

APPEARANCE & ODOR: Light golden liquid, oil odor

VAPOR DENSITY (Air=1): >5

EVAPORATION RATE (N-BUTYL ACETATE=1): >1

VOC (G/L): 0

FREEZING POINT:

SECTION X - STABILITY AND REACTIVITY

STABILITY: Stable.

CONDITIONS TO AVOID: Ignition sources.

MATERIALS TO AVOID: Oxidizers.

HAZARDOUS DECOMPOSITION PRODUCTS: Combustion: Smoke, carbon monoxide, carbon dioxide.

HAZARDOUS POLYMERIZATION: Will not occur.

SECTION XI - TOXICOLOGICAL INFORMATION

Mineral oil

LD50: 402 g/kg (skin: mouse)

SECTION XII - ECOLOGICAL INFORMATION

Not available.

SECTION XIII - DISPOSAL CONSIDERATIONS

Dispose as hazardous waste. Classification and documentation is required before disposal. Follow all local, state and federal regulations.

SECTION XIV - TRANSPORTATION INFORMATION

PROPER SHIPPING NAME: Not regulated material, liquid

HAZARD CLASS: NA

IDENTIFICATION NUMBER: NA

DOT Emergency Guide #: NA

Reportable Quantity (RQ): NA

International: NA

SECTION XV - REGULATORY INFORMATION

TSCA (Toxic Substance Control Act): Components of this product are listed on the TSCA Inventory.

CERCLA (Comprehensive Environmental Response, Compensation and Liability Act): Not listed.

SARA TITLE III (Superfund Amendments and Reauthorization Act): None listed.

CALIFORNIA PROPOSITION 65: WARNING: This product contains mineral oils, a chemical known to the State of California to cause cancer.

SECTION XVI - OTHER INFORMATION

State Right-to-Know Programs: None

NFPA Ratings

Health: 0

Flammability: 1

Reactivity: 0

HMIS Protective Equipment: X See your supervisor

Revised: 10/2001

Prepared by: Virginia KMP Corporation

Printed 09/01/2006

This information is furnished without warranty, expressed or implied, except that it is accurate to the best knowledge of Virginia KMP. The data on this sheet related only to specific material designated herein. Virginia KMP assumes no legal responsibility for use or reliance upon these data.