

**INSULATION MASTIC (revised June 2004)****Material Safety Data Sheet****SECTION I - COMPANY IDENTIFICATION****PRODUCT:** INSULATION MASTIC PM11, PM15**CAT. NO.:** PM11, PM15**DISTRIBUTED BY:**Virginia KMP Corporation  
4100 Platinum Way  
Dallas, Texas 75237**TELEPHONE NUMBERS:**Office: 1-(214) 330-7731  
Emergency Only: 1-(800) 424-9300**SECTION II - HAZARDOUS INGREDIENTS****OSHA Hazardous Components (29 CFR 1910.1200)****EXPOSURE LIMITS: 8 HR. TWA****OSHA PEL****ACGIH TLV**Asphalt (CAS# 8052-42-4)  
Silica (CAS# 14808-60-7)NE  
NENE  
NE**SECTION III - HAZARDS IDENTIFICATIONS****EMERGENCY OVERVIEW:** DANGER! Harmful if inhaled or ingested. Eye and skin irritant.**POTENTIAL HEALTH EFFECTS:****INHALATION:** Vapors may irritate respiratory tract.**EYE CONTACT:** Eye irritation develops immediately after contact.**SKIN CONTACT:** Skin irritation develops slowly after contact. May aggravate pre-existing skin disorders.**INGESTION:** Irritates gastrointestinal tract.**CHRONIC Effects:** None established.**NOTE:****CARCINOGENICITY:** LISTED IN NTP? No

IARC? No

OSHA Regulated? No

**SECTION IV - FIRST AID MEASURES****INHALATION:** Remove victim to fresh air and, if needed, immediately begin artificial respiration. Give oxygen if breathing is labored. Get emergency medical help. Contact a physician immediately.**EYE CONTACT:** Flush eyes with water for 15 minutes. Get medical attention if symptoms develop and persist.**SKIN CONTACT:** Flush with water or soap and water for 15 minutes or until all traces have been removed. Seek medical attention if symptoms develop and persist.**INGESTION:** Do not induce vomiting. Rinse mouth out with water. Get immediate medical attention.**SECTION V - FIRE FIGHTING MEASURES****FLASHPOINT (TEST METHOD):** None**FLAMMABLE LIMITS:** LOWER: NA

UPPER: NA

**AUTOIGNITION TEMPERATURE:** NA**GENERAL HAZARD:** Vapors may be produced when heated.**FIRE FIGHTING INSTRUCTIONS:** Approach fire from upwind side. Avoid breathing smoke, fumes, mist or vapors on the downwind side. Firefighters wear protective clothing and self contained breathing apparatus.**EXTINGUISHING MEDIA:** Dry powder, carbon dioxide (CO<sub>2</sub>), water fog or spray.**HAZARDOUS COMBUSTION PRODUCTS:** Smoke, vapors, carbon monoxide, carbon dioxide.**SECTION VI - ACCIDENTAL RELEASE MEASURES****LAND SPILL:** Emergency response coordinator must have mandated training. Eliminate all ignition sources. **SMALL SPILLS:** Pick up spilled materials and place in non-leaking containers; seal tightly for proper disposal or reuse. **LARGE SPILLS:** Evacuate the hazard area of unprotected personnel. Wear appropriate respirator and protective clothing. Shut off source of leak if safe to do so. Dike and contain. Remove with vacuum truck or pump to storage/salvage vessels.**WATER SPILL:** Clean up leaks/spills immediately to prevent soil or water contamination.**SECTION VII - HANDLING AND STORAGE****HANDLING:** Avoid contact with skin, eyes and clothing. After handling this product, wash hands before eating, drinking or smoking. If contact occurs, remove contaminated clothing. If needed, take first aid action shown in section IV. Launder contaminated clothing before reuse.**STORAGE:** Store in a cool place away from ignition sources. Store away from oxidizers.**SECTION VIII - EXPOSURE CONTROLS/PERSONAL PROTECTION****ENGINEERING CONTROLS:** Local exhaust ventilation recommended.**PERSONAL PROTECTION:** Respiratory protection not normally needed under proper conditions of use. Wear chemical gloves.**SECTION IX - PHYSICAL AND CHEMICAL PROPERTIES**

## INSULATION MASTIC (revised June 2004)

VAPOR PRESSURE (Air=1): 23.7 mmHg

SPECIFIC GRAVITY (H<sub>2</sub>O=1): 0.86

SOLUBILITY IN WATER: Miscible

pH: NA

BOILING POINT: 100 C

APPEARANCE & ODOR: Brownish black paste, mild asphalt odor.

VAPOR DENSITY (Air=1): 0.62

EVAPORATION RATE (BuAc=1): <1

VOC (G/L): 860

FREEZING POINT: ND

### SECTION X - STABILITY AND REACTIVITY

STABILITY: Stable

CONDITIONS TO AVOID: Heat.

MATERIALS TO AVOID: Oxidizers.

HAZARDOUS DECOMPOSITION PRODUCTS: From combustion: smoke, carbon monoxide, carbon dioxide.

HAZARDOUS POLYMERIZATION: Will not occur.

### SECTION XI - TOXICOLOGICAL INFORMATION

ND

### SECTION XII - ECOLOGICAL INFORMATION

ND

### SECTION XIII - DISPOSAL CONSIDERATIONS

Disposal per classification and documentation as required per local, state and federal regulations.

### SECTION XIV - TRANSPORTATION INFORMATION

PROPER SHIPPING NAME: Not regulated material, solid

HAZARD CLASS: NA

IDENTIFICATION NUMBER: NA

DOT Emergency Guide #: NA

Reportable Quantity (RQ): NA

International: NA

### SECTION XV - REGULATORY INFORMATION

TSCA (Toxic Substance Control Act): Components of this product are listed on the TSCA Inventory.

CERCLA (Comprehensive Environmental Response, Compensation and Liability Act): Not listed.

SARA TITLE III (Superfund Amendments and Reauthorization Act): Not listed

CALIFORNIA PROPOSITION 65: Not listed.

### SECTION XVI - OTHER INFORMATION

State Right-to-Know Programs: Not listed.

NFPA Ratings

Health: 2

Flammability: 0

Reactivity: 0

HMIS Protective Equipment: X See your supervisor

Prepared by: Virginia KMP Corporation

This information is furnished without warranty, expressed or implied, except that it is accurate to the best knowledge of Virginia KMP. The data on this sheet related only to specific material designated herein. Virginia KMP assumes no legal responsibility for use or reliance upon these data.